

PPC-GS0851T-JK4

Pictures:



Features:

1. 8" resistive touch screen(capacitive screen optional), Front panel IP65
2. Chipset: Intel® Celeron® J1900 processor
3. 2GB DDR3 RAM, up to 8 GB
4. Provide 4*USB+4*COM port
5. 2* 1000M RJ45 LAN

Specifications:

Display	Screen	8" TFT LCD
	Resolution	800*600
	Brightness	300 cd/m2
	Contrast ratio	500:1
	Touchscreen	Resistive touch screen (capacitive screen Optional)
Performance	Chipset	Intel® Celeron® J1900 Processor
	Memory	2GB DDR3 up to 8GB
	Hardware Monitor	Monitors voltage, CPU,TEMP
	Watchdog Timer	0-255 sec by software
	Storage	SSD :Standard 32GB, up to 512GB
Power	Power Supply	9-24V DC
O/S	O/S	Windows 7、Windows 10、Linux
I/O Port	USB	3*USB 2.0+1*USB3.0
	COM	4*RS232
	Ethernet	2*1000M LAN
	Audio	1*Line-out+1*Mic
	Display	1*HDMI
	MiniPCle	1*MiniPCle(optional WIFI/3G/4G)
Environmental	Anti-vibration	5-19Hz/1.0mm amplitude;19-200Hz/1.0g, acceleration
	Anti-shock	10g acceleration, 11ms duration
	IP Level	Front panel IP65
	Reliability	MTBF≥5000h; MTTR≤0.5h
	Operating Temperature	-20°C--60°C with air flow
	Storage Temperature	-30°C --70°C
	Operating Humidity	95% @40°C, non-condensing
Mechanical	Dimensions	220mm(L)*172mm(W)*43.5mm(H)
	Mounting size	VESA mounting: 100*100mm
	Material	Fanless High-strength and elegant Al-alloy panel+PPS
	Weight	1.2kg/2.5kg(NET/Gross)
	Color	Black