

PPC-GS1092T

Pictures:



Features:

1. 10.1"Multi-point capacitive touch screen
2. Chipset: RK3288 SoC Cortex-A17 Quad Core @ 1.8GHz Max.
3. Onboard 2GB EMMC (4GB optional MOQ required)
4. Provide 2*USB+4*COM port
5. Support 1*1000M LAN port

Specification:

| | | |
|----------------------|-----------------------|--|
| Display | Screen | 10.1" TFT LCD |
| | Resolution | 1280*800 |
| | Brightness | 350 cd/m2 |
| | Touchscreen | Multi-point capacitive touch screen |
| Performance | Chipset | RK3288 SoC Cortex-A17 Quad Core @ 1.8GHz Max |
| | Memory | On board 2GB EMMC (4GB optional MOQ required) |
| | Hardware Monitor | Monitors voltage,CPU, TEMP |
| | Watchdog Timer | 0-255 sec by software |
| | Storage | 8GB NAND Flash |
| Power | Power Supply | 12V DC (with adapter) |
| O/S | O/S | Android 5.1.1 |
| I/O Port | USB | 2*USB 2.0 |
| | COM | 4*RS232 (1*RS485 optional) |
| | Ethernet | 1*1000M LAN |
| | Audio | 1*Line-out/In |
| | Display | 1*HDMI |
| | Bluetooth/WIFI | Bluetooth 4.0/WIFI |
| | GPS | Optional |
| | SD/TF | 1*TF card slot(Max capacity up to 128G) |
| | SIM | 1*SIM card slot |
| | MiniPCle | 1*MiniPCle(optional 3G/4G) |
| Environmental | Anti-vibration | 5-19Hz/1.0mm amplitude;19-200Hz/1.0g, acceleration |
| | Anti-shock | 10g acceleration, 11ms duration |
| | IP Level | Front panel IP65 |
| | Reliability | MTBF≥5000h; MTTR≤0.5h |
| | Operating Temperature | -10℃--50℃ with air flow |
| | Storage Temperature | -20℃ --60℃ |
| | Operating Humidity | 95% @40℃, non-condensing |
| Mechanical | Dimensions | 268mm(L)*195mm(W)*52.5mm(H) |
| | Mounting size | VESA mounting: 100*100mm Embedded mounting: 243*155mm |
| | Material | Fanless High-strength and elegant Al-alloy panel |
| | Weight | 1.45kg/2.31kg(NET/Gross) |
| | Color | Black |